



PROFILE SERIES

Pr300/Pr300UX

Description

The Profile Pr300 Series provides an ideal balance of high fidelity and high design. Custom built to match the exact height and finish of any display, the Profile Pr300 and Pr300UX pair perfectly with 40"-50" displays in smaller rooms and boardrooms. The shallow depth cabinets are equipped with high-fidelity 3" drivers and are available with audiophile-grade 1" cloth-dome tweeters to provide accurate sound reproduction at all volumes.

Key Features

- Custom crafted to match the exact height and finish of any display
- As thin as 2" deep to ensure compatibility with flat-screen TVs
- Easily mounts to articulating TVs or to the wall with Leon's brackets
- Available as a stereo pair or multichannel speakers
- Solid MDF construction, handcrafted in the USA

Recommended Pairings: AxV60, Ds400, ACS8-400



COMPARE MODELS

	Pr300	Pr300UX
HEIGHT	Exact height of TV	Exact height of TV
WIDTH	5"	5"
DEPTH	2.75" (3" with grill)	2" (2.25" with grill)
MATERIAL	MDF Enclosure	MDF enclosure
WEIGHT	15-30 lbs.	15-30 lbs.
FINISH	Match TV color (or any custom finish)	Match TV color (or any custom finish)
GRILL	Standard woven fabric	Standard woven fabric
CONNECTIONS	Spring-loaded terminals	Spring-loaded terminals
COMPONENTS	3" woofers; 1" tweeters	3" ultra-thin woofers; 1" silk-dome tweeters
IMPEDANCE	L/R: 6Ω; -MC: 4Ω	L/R: 6Ω; -MC: 4Ω
REC. POWER	L/R: 50-150W	L/R: 25-125W
MAX. OUTPUT	L/R: 98dB avg, 104dB peak	L/R: 98dB avg; 104dB peak
COVERAGE	L/R: Hor: 140°; Vert: 110°	L/R: Hor: 140°; Vert: 110°
FREQ. RESP.	L/R: 125Hz - 20kHz	L/R: 120-20kHz
SENSITIVITY	L/R: 85dB @ 2.83V/1m	L/R: 86dB @ 2.83V/1m
CONFIGURATIONS	Pr300, Pr300-MC	Pr300UX, Pr300UX-MC

MOUNTING BRACKETS Works with: PrSMB, PrMMB, PrTTS